

Switches



LANCOM GS-2326+

Managed 26-port Gigabit Ethernet switch for reliable networks

The LANCOM GS-2326+ is a reliable component for modern network infrastructures for any industry or application. It networks up to 26 devices with its 24 Gigabit Ethernet ports and 2 combo ports (Ethernet or fiber-optic). Equipped with numerous security features and a high-performance hardware platform, it is ideal for the secure and reliable networking of medium-sized networks.

- › 24 Gigabit Ethernet and 2 combo ports (TP/SFP)
- › Security with configurable access control on all ports based on IEEE 802.1X
- › Secure remote management through TACACS+, SSH, SSL, and SNMPv3
- › Convenient integration into LANCOM monitoring systems
- › IPv6 and IPv4 support for modern enterprise networks
- › 5-year warranty on all components

LANCOM GS-2326+

High power output on 26 ports

The LANCOM GS-2326+ is equipped with 24 Gigabit Ethernet ports and 2 combo ports (Ethernet or fiber-optic). With a data throughput of 52 Gbps on the backplane, it offers full performance even under load. This makes the switch a high-performance basis for modern network infrastructures in any industry or field of application.

Configurable access control

The LANCOM GS-2326+ excludes rogue clients from gaining unauthorized access to the network. This is ensured by secured access control on all ports as per IEEE 802.1X (port-based, single, multi, and MAC-based).

Secure remote management

Secure communication protocols such as SSH, SSL and SNMPv3 mean that the LANCOM GS-2326+ is ideal for professional remote network management. The switch also supports the TACACS+ protocol for authentication, authorization, and accounting. This optimized solution promises maximum security for multi-site network management and monitoring.

Integration into LANCOM monitoring systems

The LANCOM GS-2326+ integrates seamlessly into existing LANCOM network infrastructures. Network events are easy to monitor with the LANCOM monitoring systems LANCOM Large Scale Monitor and LANmonitor.

IPv6 and IPv4 support

Thanks to the dual-stack implementation, the LANCOM GS-2326+ operates in pure IPv4, pure IPv6, or in mixed networks. Applications such as SSL, SSH, Telnet, and TFTP can continue to be operated on IPv6 networks. Supported IPv6 features include stateless auto-configuration, the discovery of neighboring devices, and MLD snooping.

Zero-touch deployment

Quick and easy network integration of the switch as well as automatic assignment of the configuration—without manual configuration. For installations based on the LANCOM Management Cloud, switch receives the correct configuration immediately after network authentication.

LANCOM GS-2326+

Security	
Secure Shell Protocol (SSH)	SSH for a secure remote configuration
Secure Sockets Layer (SSL)	SSL to encrypt HTTP connections; advanced security for browser-based configuration via web interface
IEEE 802.1X	IEEE 802.1X access control on all ports; RADIUS for authentication, authorization and accounting with MD5 hashing; guest VLAN; dynamic VLAN assignment
Private VLAN edge	Layer 2 isolation between clients in the same VLAN ('protected ports'); support multiple uplinks
Port security	Locking of MAC addresses to ports; limiting of the number of learned MAC addresses
IP source guard	Blocking access for illegal IP addresses on specific ports
Access control lists	Drop or rate limitation of connections based on source and destination MAC addresses, VLAN ID, IP address (IPv4/IPv6), protocol, port, DSCP/IP precedence, TCP/UDP source and destination ports, IEEE 802.1p priority, ICMP packets, IGMP packets, TCP flag
RADIUS/TACACS+	Authentication, authorization and accounting of configuration changes by RADIUS or TACACS+
Storm Control	Multicast/Broadcast/Unicast storm suppression
Isolated Group	Allows certain ports to be designated as protected. All other ports are non-isolated. Traffic between isolated group members is blocked. Traffic can only be sent from isolated group to non-isolated group.
Performance	
Switching technology	Store and forward with latency less than 4 microseconds
MAC addresses	Support of max 8K MAC addresses
Throughput	Max. 52 Gbps on the backplane
Maximum packet processing	38.69 million packets per second (mpps) at 64-byte packets
Single IP Management (SIP)	Supports stacking of up to 16 devices, several switches can be managed via one ip address
VLAN	Port based and IEEE 802.1q tag based VLAN with up to 4,096 VLAN and up to 4,000 active VLANs; Supports ingress and egress packet filter in port based VLAN
Jumbo frame support	Jumbo frame support with up to 9k frames
Energy efficiency (Green Ethernet)	
Energy detection	Energy efficiency according to IEEE 802.3az. Automatically turns off power on Gigabit Ethernet RJ-45 port when detecting link down or Idle of client. Active mode is resumed without loss of any packets when the switch detects the link up
Cable length detection	Adjusts the signal strength based on the cable length. Reduces the power consumption for short cable
Layer 2 switching	
Spanning Tree Protokoll (STP) / Rapid STP / Multiple STP	Standard Spanning Tree according to IEEE 802.1d with fast convergence support of IEEE 802.1w (RSTP); using Multiple Spanning Tree instances by default according to IEEE 802.1s (MSTP)
Link Aggregation Control Protocol (LACP)	Support of 13 groups containing up to 16 ports each according to IEEE 802.3ad
VLAN	Support for up to 4K VLANs simultaneously (out of 4096 VLAN Ids); matching due to port, IEEE 802.1q tagged VLANs or MAC addresses
Voice VLAN	Voice traffic is automatically assigned to a voice-specific VLAN and treated with appropriate levels of QoS
IGMP multicasts	IGMP v1, v2, v3 to limit bandwidth-intensive multicast traffic to ports with requesters; supports 256 multicast groups; source-specific multicasting
IGMP querier	Support of multicast domains of snooping switches in the absence of a multicast router
IGMP proxy	IGMP proxy to pass IGMP messages through
Generic VLAN registration	VLAN registration with GVRP according to IEEE 802.1q for automatic delivery of VLANs in bridged domains
DHCP Relay Agent	Relay of DHCP broadcast request to different LANs
Supported DHCP options	<ul style="list-style-type: none"> > DHCP option 66 > DHCP option 67 > DHCP option 82

LANCOM GS-2326+

Interfaces	
Ethernet	<ul style="list-style-type: none"> > 24 TP ports 10/100/1000 Mbps > 2 combo ports (TP/SFP) with 100/1000 Mbps (SFP) and 10/100/1000 Mbps (TP) > 26 concurrent Ethernet ports in total
Console port	RJ45 configuration port for command line access
Management and monitoring	
Management	LANconfig, WEBconfig, LANCOM Management Cloud
Command Line Interface (CLI)	Configuration and status display from the command line with console application and direct connection to console port, via Telnet or SSH
Monitoring	LANmonitor, LANCOM Management Cloud
Remote Monitoring	Integrated RMON software agent supports 4 RMON groups (history, statistics, alarms and events) for enhanced traffic management, monitoring and analysis
Easy-Configuration-Ports	Easy setup of ports for QoS and Security based on pre-defined configuration profiles
Port Mirroring	Traffic can be mirrored from on port to another for investigation with network analyzer or RMON probe. Up to 25 ports can be mirrored to a single mirror port. Single sessions can be selected
Security	Access rights (read/write) can be set up separately, access control list
SNMP	SNMP management via SNMPv1, v2c or v3 with support of traps. User-based security model for SNMPv3 (USM)
Diagnosis	Diagnosis from the switch with PING and cable diagnosis
Firmware update	<ul style="list-style-type: none"> > Update via WEBconfig and browser (HTTP/HTTPS) > Update via TFTP and LANconfig > Dual firmware image to update during operation
Secure Copy	Securely import and export files
DHCP client	Automatic assignement of the management IP address by DHCP
SNTP	Automatic time settings with Simple Network Time Protocol (SNTP)
s-flow	Standard for monitoring of high-speed-networks. Visualization of network use, accounting an analysisation to protect your network against dangers
Hardware	
Weight	5,50 lbs (2,50 kg)
Power supply	Internal power supply unit (100 – 240 V, 50 – 60 Hz)
Environment	Temperature range 0 – 40° C; humidity 10 – 90%; non-condensing
Housing	Robust metal housing, 19" 1U (442 x 44 x 170,3 mm > W x H x D) with removable mounting brackets, network connectors on the front
Housing	Robust metal housing, 19" 1U (442 x 44 x 170,3 mm > W x H x D) with removable mounting brackets, network connectors on the front
Fans	None; fanless design without rotating parts, high MTBF
Power consumption (max)	26 W
Software	
Software Lifecycle Management	<p>Following the official announcement of a product's discontinuation by means of the LANCOM price list, during an existing LANCOM warranty you will receive:</p> <ul style="list-style-type: none"> > For 2 years: free updates to the operating system, including new features and other updates with general improvements > For 2 years: critical security fixes based on the last applicable firmware version > For 5 years: free technical manufacturer support
Anti-backdoor policy	Products from LANCOM are free of hidden access paths (backdoors) and other undesirable features for introducing, extracting or manipulating data. The Trust Seal "IT Security made in Germany" (ITSMIG) and certification by the German Federal Office for Information Security (BSI) confirm the trustworthiness and the outstanding level of security

LANCOM GS-2326+

Declarations of conformity*	
CE	EN 60950-1, EN 55022, EN 55024
FCC	FCC Part 15 (CFR47) Class A
Country of origin	Software designed in Germany, Assembled in Taiwan
*) Note	You will find all declarations of conformity in the products section of our website at www.lancom-systems.com
Supported IEEE standards	
IEEE 802.1AB	Link Layer Discovery Protocol (LLDP)
IEEE 802.1AB	LLDP-MED
IEEE 802.1ad	Q-in-Q tagging
IEEE 802.1d	MAC Bridging
IEEE 802.1d	Spanning Tree
IEEE 802.1p	Class of Service
IEEE 802.1q	VLAN
IEEE 802.1s	Multiple Spanning Tree Protocol (MSTP)
IEEE 802.1w	Rapid Spanning Tree Protocol (RSTP)
IEEE 802.1X	Port Based Network Access Control
IEEE 802.3	10Base-T Ethernet
IEEE 802.3ab	1000Base-TX Ethernet
IEEE 802.3ad	Link Aggregation Control Protocol (LACP)
IEEE 802.3az	Energy Efficient Ethernet
IEEE 802.3u	100Base-T Ethernet
IEEE 802.3x	Flow Control
IEEE 802.3z	1000Base-X Ethernet
Supported RFC standards	
RFC 854	Telnet Protocol Specification
RFC 1213	MIB II
RFC 1215	SNMP Generic Traps
RFC 1493	Bridge MIB
RFC 1769	Simple Network Time Protocol (SNTP)
RFC 2021	Remote Network Monitoring MIB v2 (RMONv2)
RFC 2233	Interface MIB
RFC 2613	SMON MIB
RFC 2617	HTTP Authentication
RFC 2665	Ethernet-Like MIB
RFC 2674	IEEE 802.1p and IEEE 802.1q Bridge MIB
RFC 2818	Hypertext Transfer Protocol Secure (HTTPS)
RFC 2819	Remote Network Monitoring MIB (RMON)
RFC 2863	Interface Group MIB using SMIv2
RFC 2933	IGMP MIB
RFC 3019	MLDv1 MIB
RFC 3414	User based Security Model for SNMPv3

LANCOM GS-2326+

Supported RFC standards	
RFC 3415	View based Access Control Model for SNMP
RFC 3635	Ethernet-Like MIB
RFC 3636	IEEE 802.3 MAU MIB
RFC 4133	Entity MIBv3
RFC 4188	Bridge MIB
RFC 4251	The Secure Shell Protocol Architecture (SSH)
RFC 4668	RADIUS Authentication Client MIB
RFC 4670	RADIUS Accounting MIB
RFC 5519	Multicast Group Membership Discovery MIB
Scope of delivery	
Manual	Printed Installation Guide (DE/EN)
Cable	Serial configuration cable, 1.5m
Cable	IEC power cord
19" brackets	Two 19" brackets for rackmounting
Support	
Warranty	5 years, support via hotline and Internet KnowledgeBase
LANCOM Warranty Advanced Option S	Option for replacement of a defective device, item no. 10715
LANCOM Management Cloud	
LANCOM LMC-B-1Y LMC License	LANCOM LMC-B-1Y License (1 Year), enables the management of one category B device for one year via the LANCOM Management Cloud, item no. 50103
LANCOM LMC-B-3Y LMC License	LANCOM LMC-B-3Y License (3 Years), enables the management of one category B device for three years via the LANCOM Management Cloud, item no. 50104
LANCOM LMC-B-5Y LMC License	LANCOM LMC-B-5Y License (5 Years), enables the management of one category B device for five years via the LANCOM Management Cloud, item no. 50105
Accessories	
1000Base-SX SFP module	LANCOM SFP-SX-LC1, item no. 61556
1000Base-LX SFP module	LANCOM SFP-LX-LC1, item no. 61557
LANCOM Power Cord (UK)	IEC power cord, UK plug, item no. 61650
LANCOM Power Cord (CH)	IEC power cord, CH plug, item no. 61652
LANCOM Power Cord (US)	IEC power cord, US plug, item no. 61651
LANCOM Power Cord (AU)	IEC power cord, AU plug, item no. 61653
Item number(s)	
LANCOM GS-2326+	61483

