

LANCOM OAP-380 PSU


Quick Reference Guide



LANCOM

Mounting

 \bigotimes



(3) Connect the output cable (B) of the LANCOM OAP-380 PSU with the voltage input connector on the LANCOM OAP-382. Leave some slack in the cable to compensate for heat-induced changes in the cable length. Arrange the cable such that the lowest point of the loop encourages water to flow away and not get into the housing.

(4) Insert the power plug (A) of the LANCOM OAP-380 PSU into an available 230V outlet.

The power plug of the LANCOM OAP-380 PSU is IP44 splash proof. Avoid exposure to direct weathering.

The housing of the LANCOM OAP-380 PSU may only be opened by gualified technicians.

LANCOM OAP-380 PSU

ш

U

>

ш

ш

H

G

Ζ

H

 \cup

ш

Ζ Ζ

0

 \cup

Ζ

4

G

Ζ

-

Ζ

0

 $\widehat{(1)}$ Use the 4 screws (supplied) to at-

of the LANCOM OAP-380 PSU.

(2) Fix the LANCOM OAP-380 PSU and

its mounting plate to the wall with

the 2 bolts supplied. Mount the

LANCOM OAP-380 PSU with the

ports facing downwards.

tach the mounting plate to the rear

- Outdoor housing for a temperature range of -10 to 40°C
- Incl. wall-mounting bracket
- 3 year warranty



Overload protect Environment

Ambient tempe (operating) Protection ratin

Certifications CE

Package conte

Power adapter Cable

Mounting mate Documentation Warranty

Manufacturer w Item descripti

61692 61693





Supplies 230 volts to the LANCOM OAP-382.

- 48-volt power supply unit with prefabricated cable

The LANCOM OAP-380 PSU (Power Supply Unit) is a complete power supply kit that makes it easy to install the outdoor access point LANCOM OAP-382 at a 230 V power source. The IP66 housing and extended temperature range make the power supply suitable for indoor or outdoor installation. The supplied wall-mount bracket makes light work of wall mounting.

/ unit spe	ecifications	
	Voltage	48 V DC
	Current	0.8 A
	Current range	0 to 0.8 A
	Power rating	37 W
	Voltage range	88 to 264 V AC,
		125 to 373 V DC,
	Frequency	47 to 63 Hz
	Efficiency	86% at 230V AC
	Starting current	Cold start 36A/230 V
ection	at 0.9 A to 1.1 A	
erature	-10°C to +40°C	
ng	Outdoor IP66 housing	
;		
	60950-22	
	55022 class B 55024	
tent	55024	
	48 V power supply unit in IP66 housing	
	3 m power cable with IP44 splash-proof plug	
	15 m outdoor-rated power cable with 48V conne	ector to LANCPM OAP-382
erial	Wall mounting plate with bolts and dowels	
n	Hardware Quick Reference Guide, Support flyer	
warranty	LANCOM supplies this power supply with a 3-year manufacturer's warranty.	
ion		
	LANCOM OAP-380 PSU (EU)	
	LANCOM OAP-380 PSU (UK)	