



	UF-T60	UF-60 / UF-60 LTE	UF-160	UF-260	UF-360	UF-760
Item no.	55004	55002 / 55003	55012	55024	55036	55035
Category	Industrial	Desktop	Desktop	Desktop	Rack	Rack
Hardware properties						
Ports	5x GE copper, 2x SFP	4x GE copper	4x GE copper	4x GE copper, 1x SFP	6x GE copper, 2x SFP+	8x GE copper, 2x SFP+
Modem	-	LTE Advanced (only UF-60 LTE)	-	-	-	-
Power supply & memory redundancy	-	-	-	-	-	✓
Opt. extension modules *	-	-	-	-	✓ 1G ETH, 1G SFP, 10G SFP+	✓ 1G ETH, 1G SFP, 10G SFP+, 40G QSFP+
Mounting options	DIN rail mounting	Opt. LANCOM Firewall Rack Mount UF-60 (55128)	Opt. LANCOM Firewall Rack Mount UF-160/260 (55125)	Opt. LANCOM Firewall Rack Mount UF-160/260 (55125)	Installation angle	Extension rails
Max. system performance (individual measurements) **						
IDS / IPS throughput HTTPS (Mbps)	1,150	700	750	1,250	1,400	13,000
Firewall throughput TCP (Mbps)	3,700	3,500	3,550	4,450	11,600	49,830
VPN throughput IPSec (Mbps)	1,200	790	1,200	1,500	2,200	19,700
Concurrent sessions	1,000,000	1,000,000	1,000,000	2,000,000	4,000,000	16,700,000
Max. system performance (usage of all UTM functionalities) **						
UTM throughput HTTPS (Mbps)	200	150	170	340	420	3,400
Recommended number of VPN tunnels	25 – 50	5 – 25	25 – 50	100 – 200	200 – 1,000	1,000 – 5,000
Power						
Input voltage (V)	12 – 36	100 – 240	100 – 240	100 – 240	100 – 240	100 – 240
Max. power consumption (W)	22.3 (redundant ausgelegt)	40	40	40	60	300 (redundant ausgelegt)
Dimensions						
B x H x T (mm)	130 × 100 × 150	232 × 44 × 115 (without antennas for UF-60 LTE)	231 × 44 × 200	231 × 44 × 200	440 × 44 × 269	440 × 44 × 364

* Compatible LANCOM UF Extension Modules can be found on the [product website](#).

** All throughput rates measured bidirectionally with 1,500 bytes packet size.

You can find the service and support portfolio at www.lancom-systems.com/service-support or in the [service & support overview](#).

For operation in a virtualized environment, the LANCOM vFirewall is also available with the same range of security functions as the hardware-based Unified Firewalls. Find out more at: www.lancom-systems.com/vfirewall

A valid operating license is required for all LANCOM R&S® Unified Firewalls and LANCOM vFirewalls (Basic or Full for 1, 3, or 5 years).