



. . . c o n n e c t i n g   y o u r   b u s i n e s s

## LANCOM ES-1108P

8-port unmanaged 10/100 Mbps Fast Ethernet switch with four PoE ports

- 8-port unmanaged 10/100 Mbps Ethernet switch
- 4x Power over Ethernet compliant to IEEE 802.3af
- 15.4 W per PoE port possible
- Automatic detection of PoE devices and consumption
- Adapters for mounting in 19"-cabinets

Customised to support the LANCOM product portfolio, the LANCOM Ethernet Switch ES-1108P is the optimal component for structured cabling of home offices and smaller offices. Four power-over-Ethernet ports ensure maximum flexibility in positioning PoE-compliant VoIP telephones and access points.

All of the adapters necessary for mounting in 19" cabinets are supplied. This ensures that the LANCOM ES-1108P can be fully integrated into existing infrastructures.

# LANCOM ES-1108P

Standards	
Media	10Base-T: UTP Cat. 3, 4, 5 or better 100Base-TX: UTP Cat. 5 or better
IEEE	IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX IEEE 802.3af
Operating modes	
Switching	Store and forward
Auto MDI/MDI-X	Yes
Transfer mode	10/100 Mbps, full/half duplex (auto-sensing)
Transfer rate	10 Mbps: 14.880 pps (64-byte packets) 100 Mbps: 148.800 pps (64-byte packets)
Flow control	IEEE 802.3x flow control in full-duplex mode Back-pressure flow control in half-duplex mode
Display	LEDs: Power, Link/Act, Speed, PoE activity
Hardware	
Power supply	100V – 240V AC, internal power supply unit
Environment	Temperature range 0 – 40°C; humidity 5 – 90 %; non-condensing
Housing	Metal housing, connections on the front; measures 220 x 44 x 130.5 mm (W x H x D)
Power consumption (max.)	ca. 65 Watt
Weight	1 kg
Declarations of conformity	
CE	EN 55022, EN 55024
Package content	
Cable	IEC cable
Manual	Printed Quick Installation Guide (DE/EN)
Adapters	19" adapters incl. mounting materials (two angles)
Item numbers	
LANCOM ES-1108P	61450
LANCOM ES-1108P (UK)	61449
Service	
Warranty	2 years
Support	Via hotline and Internet